

USB 3.0 B Panel Mount Extension Cable, Male to Female



Description:

FARSINCE High Quality USB 3.0 B Male to B Female Panel Mount Cable is the perfect solution for combining two USB Type-B cables to achieve connectivity through a panel. This allows the user to provide connectivity from a source that is contained within a secure location. USB 3.0 B Panel Mount Extension Cable is short and designed for minimal signal loss.

It provides a transfer rate up to 5 Gbps depending upon the peripheral's USB version, and easily attaches to any USB device. Flexible PVC jacket, Foil and braid shielding, and the twisted pair construction make a better performance.

Item no. FSP1075

Specification:

- Connector 1: USB 3.0 B male
- Connector 2: USB 3.0 B female with screw locking
- Gold plated contact, Nickel plated shell
- Nut and Screw type: M3 nickel plated
- Hole Pitch: 30 ± 0.5 mm
- Cable Conductor: Bare Copper
- Wire Gauge: 28/28/24AWG
- Outer Diameter: 5.5 ± 0.2 mm
- Shielding: Aluminum foil, Braiding
- Housing: Injection molding
- Jacket: PVC
- Support super speed USB 3.0 devices and the transfer rate reaches to 5 Gbps
- Backward compliant with high-speed USB 2.0 (480Mbps), full-speed USB 1.1 (12 Mbps), and low speed USB 1.0 (1.5 Mbps)
- Compliance: RoHS, REACH

Order Informaiton:

- FSP1075: USB 3.0 B male to B female Panel Mount Cable, 0.3m, 28AWG, OD 5.5 ± 0.15 mm