

## USB 3.0 A to USB C Male Panel Mount Cable with Dual Screw



### Description:

FARSINCE High Quality USB 3.0 A male to USB C male Panel mount cable with dual screw is the perfect solution for combining USB Type-A and USB Type-C cables to achieve connectivity through a panel. This allows the user to provide connectivity from a source that is contained within a secure location. USB 3.0 A to USB C Male Panel Mount Cable is short and designed for minimal signal loss.

It provides a transfer rate up to 5 Gbps depending upon the peripheral's USB version, and easily attaches to any USB device. Flexible PVC jacket, Foil and braid shielding, and the twisted pair construction make a better performance.

**Item no. FSP1081**

### Specification:

- Connector 1: USB 3.0 A male
- Connector 2: USB Type-C male with dual screw locking
- Gold plated contact, Nickel plated shell
- Nut and Screw type: M2 nickel plated
- Hole Pitch:  $15 \pm 1$ mm
- Cable Conductor: Tinned Copper
- Insulation: Foamed PE SKIN/HDPE
- Wire Gauge: 30/30/22AWG OD:  $4.5 \pm 0.2$ mm for 0.5M-3M; 28/28AWG OD: 5.5mm for 5M
- Shielding: Aluminum foil, Braiding
- Housing: Injection molding
- Jacket: PVC
- USB Power Delivery up to 3A
- Support super speed USB 3.0 devices and the transfer rate reaches to 5 Gbps
- Backward compliant with high-speed USB 2.0 (480Mbps), full-speed USB 1.1 (12 Mbps), and low speed USB 1.0 (1.5 Mbps)
- Compliance: RoHS, REACH

### Order Informaiton:

- FSP1081-005: 0.5m, 30/30/22AWG, OD $4.5 \pm 0.2$ mm
- FSP1081-010: 1.0m, 30/30/22AWG, OD $4.5 \pm 0.2$ mm
- FSP1081-018: 1.8m, 30/30/22AWG, OD $4.5 \pm 0.2$ mm
- FSP1081-030: 3.0m, 30/30/22AWG, OD $4.5 \pm 0.2$ mm
- FSP1081-050: 5.0m, 28/28AWG, OD5.5mm