

## Waterproof USB Panel Mount USB A and USB C Male to Female Car Cable



**Item no. FSP4015**

### Description:

FARSINCE High Quality Waterproof USB Panel Mount USB A and USB C Male to Female Car Cable is the perfect solution for expanding USB Type-A and USB Type-C ports on the dashboards of cars, trucks, motorcycles, boats, yachts, etc. Equipped with M26 x 1.5 aluminum nut, just use an existing hole or cut a new hole on the dashboard and fix it with the nut, USB Type-A, and USB Type-C ports extension.

Equipped with a waterproof and dustproof cover, suitable for outdoor use, which can prevent rain or debris from entering the interior and causing damage to the connector.

### Specification:

- Connector 1: USB 3.0 Type-A male, USB 3.0/3.1 Type-C male
- Connector 2: USB 3.0 Type-A female, USB 3.0/3.1 Type-C female
- Gold plated contact, Nickel plated shell
- Cable Conductor: Bare Copper
- Wire Gauge: 28/28/24AWG for USB 3.0 Type-A OD5.5mm; 30/30/24AWG for USB 3.0 Type-C OD4.5mm; 32/32/24AWG for USB 3.1 Type-C OD4.5mm
- Shielding: Aluminum foil, Braiding
- Housing: Injection mold
- Jacket: PVC
- USB 3.1 Type-C support transfer rate reaches to 10 Gbps, Video resolution up to 4K@60Hz
- Support super speed USB 3.0 devices and the transfer rate reaches to 5 Gbps
- Compliance: RoHS, REACH

### Order Information:

- FSP4015A-010: 1.0m, USB 3.0 A and USB 3.0 C male to female flush panel mount Car Waterproof Cable, 28/28/24AWG for USB 3.0 Type-A OD5.5mm; 30/30/24AWG for USB 3.0 Type-C OD4.5mm
- FSP4015A-020: 2.0m, USB 3.0 A and USB 3.0 C male to female flush panel mount Car Waterproof Cable, 28/28/24AWG for USB 3.0 Type-A OD5.5mm; 30/30/24AWG for USB 3.0 Type-C OD4.5mm
- FSP4015B-010: 1.0m, USB 3.0 A and USB 3.1 C male to female flush panel mount Car Waterproof Cable, 28/28/24AWG for USB 3.0 Type-A OD5.5mm; 32/32/24AWG for USB 3.1 Type-C OD4.5mm
- FSP4015B-020: 2.0m, USB 3.0 A and USB 3.1 C male to female flush panel mount Car Waterproof Cable, 28/28/24AWG for USB 3.1 Type-A OD5.5mm; 32/32/24AWG for USB 3.1 Type-C OD4.5mm